

# Specifications :

● = Standard equipment    ○ = optional equipment

		ACTIVA 7244	ACTIVA 7245	ACTIVA 7246
<b>Table and main crop elevator</b>				
Cutting widths available	m	4.20 to 6.00	4.80 to 6.00	4.80 to 6.60
Reel drive		Mechanical Variator		
Table and elevator reverser		Standard		
Table features		Automatic cutting height control		
Auto Level		○	○	○
<b>Cylinder</b>				
No. of bars				8
Width / Diameter	mm/mm	1340 / 600	1340 / 600	1600 / 600
Speed range	rev/min	380 to 1210	380 to 1210	430 to 1310
<b>Concave</b>				
No. of bars		12		
Wrap angle	degrees	106		
Extra wrap angle provided by ABC module	degrees	14		
Area	m <sup>2</sup>	0.83	0.83	0.99
<b>ABC Module</b>				
3-position adjustment		●	●	●
<b>Straw walkers</b>				
No. / No. of steps		5 / 4	5 / 4	6 / 4
Separation area	m <sup>2</sup>	5.73	5.73	6.81
<b>Shaker shoe</b>				
Grain pan with high dividers		●	●	●
2 adjustable sieves + extensions		●	●	●
Total area	m <sup>2</sup>	4.67	4.67	5.58
Type of fan		Volumetric blade type fan		
Fan speed	rev/min	350 to 1050		
Returns to cylinder		●	●	●
Fan speed adjustment		Electrical, in cab		
<b>Grain tank</b>				
Capacity	litre	7000	7000	7500
Unloading rate	l/sec	85	85	85
Auger length	m	4	4	4
Unloading height	m	4.18	4.21	4.21

		ACTIVA 7244	ACTIVA 7245	ACTIVA 7246
<b>Residue handling</b>				
Straw chopper		●	●	●
Electric deflectors for the straw chopper hood		○	○	○
Chaff spreader		○	○	○
<b>Engine</b>				
Make/type		IVECO NEF	IVECO NEF	IVECO NEF
Capacity	litre	5.8	5.8	5.8
Power (ISO)	hp/kW	220 / 160	255 / 186	255 / 186
Fuel tank capacity	litre	450	450	450
<b>Transmission</b>				
Type / No. gears		Hydrostatic / 3	Hydrostatic / 3	Hydrostatic / 3
<b>Tyres</b>				
Front		620/75 R30	650/75 R 32	650/75 R 32
Rear		16.0/70-20	460/70 R24	460/70 R24
Front optional		650/75 R 32	620/75 R34	620/75 R34
Front optional		800/65 R 32	800/65 R 32	800/65 R 32
Rear optional		460/70 R24		
<b>Cab</b>				
XL with heater, air conditioning, electrically controlled and heated rear view mirrors, mechanical seat, adjustable steering column, Agritronic monitor unit.				
<b>Options</b>				
High performance top sieve for maize		○	○	○
Fan speed reduction	rev/min	_____ 270 to 840, option _____		
<b>Sizes</b>				
Overall length without table	mm	8370	8370	8370
Width without table, 650/75R32 tyres	mm	3280	3280	3560
Weight without table	kg	10100	13650	12950
<b>Accessories</b>				
<b>On request</b>				
		_____	Chaff spreader	_____
		_____	Maize kit, pea kit	_____
		_____	4WD rear axle	_____
		_____	Multi-coupler	_____