

Specifications

● = Standard equipment

○ = optional equipment

		BETA 7260	BETA 7270	BETA 7260 AL	BETA 7270 AL
Table and main crop elevator					
Cutting widths available	m	4.80 to 6.60	5.40 to 6.60	4.80 to 6.60	5.40 to 6.60
Reel drive		Mechanical Variator			
Table and elevator reverser		Standard			
Table features		Automatic cutting height control			
Auto Level		●	●	●	●
Powerfeed Roller		●	●	●	●
Hi-inertia cylinder					
No. of bars		8 + 8 ballast bars			
Width / Diameter	mm	1340 / 600	1600 / 600	1340 / 600	1600 / 600
Speed range	rev/min	380 to 1210	430 to 1310	380 to 1210	430 to 1310
Concave					
No. of bars		12			
Wrap angle	degrees	106			
Area	m ²	0.83	0.99	0.83	0.99
Rotary separator					
Width / Diameter	mm	1310 / 600	1560 / 600	1310 / 600	1560 / 600
Separator concave					
No. of bars		8			
Wrap angle		57			
Area	m ²	0.46	0.54	0.46	0.54
Rotating concave system		●	●	●	●
Straw walkers					
No. / No. of steps		5 / 4	6 / 4	5 / 4	6 / 4
Separation area	m ²	6.7	8	6.7	8
Shaker shoe					
Grain pan with high dividers		●	●	●	●
2 adjustable sieves + extensions		●	●	●	●
Total area	m ²	4.67	5.58	4.67	5.58
Type of fan		Full width blade type fan			
Fan speed	rev/min	350 to 1050			
Returns to cylinder		●	●	●	●
Fan speed adjustment		Electrical, in cab			

		BETA 7260	BETA 7270	BETA 7260 AL	BETA 7270 AL
Grain tank					
Capacity	litre	9000	9000	8200	8200
Unloading rate	l/sec	105	105	105	105
Auger length	m	5	5	5	5
Unloading height	m	4.45	4.45	4.45	4.45
Residue handling					
Straw chopper		●	●	●	●
Straw chopper hood with electrical deflectors		○	○	○	○
Chaff spreader		○	○	○	○
Engine					
Make/type		SISU / 74 ETA	SISU / 84 ETA	SISU / 74 ETA	SISU / 84 ETA
Capacity	litre	7.4	8.4	7.4	8.4
Power (ISO)	hp/kW	275 / 202	305 / 225	275 / 202	305 / 225
Fuel tank capacity	litre	450	450	450	450
Transmission					
Type / No. gears		Hydrostatic / 4	Hydrostatic / 4	Hydrostatic / 4	Hydrostatic / 4
Tyres					
Front		800/65 R 32	800/65 R 32	650/75 R 32	650/75 R 32
Rear		460/70 R 24	460/70 R 24	460/70 R 24	460/70 R24
Front optional		650/75 R 32	650/75 R 32		
Front optional		710/75 R 34	710/75 R 34		
Cab XLR with heater, air conditioning, electrically controlled rear view mirrors, air suspended seat, 3D steering column, Agritronicplus monitor system					
Options					
Auto Level Combine Option		○	○	●	●
High performance top sieve for maize		○	○	○	○
Fan speed reduction	rev/min	270 to 840, option			
Dimensions					
Overall length without table	mm	8370	8370	8560	8560
Width without table, standard tyres	mm	3585	3850	3540	3815
Weight	kg	12450	13650	12950	14150
Accessories On request					
4WD rear axle (standard on Auto Level version), fan speed reduction, maize kit, pea and bean kit.					