

MF 3600 Specifications: ● = Standard ○ = Optional - = Not applicable/available

		MF 3615	MF 3625	MF 3635	MF 3645
Engine power					
@ 2150 rpm	* ISO hp (kW)	58 (43)	68 (51)	78 (58)	91 (68)
Max. torque @ rpm	* Nm	245/1400	279/1400	312/1400	350/1400
* ISO TR14396					
Engine					
Water cooled, direct injection diesel	make type	SisuDiesel 33DT	SisuDiesel 33DT	SisuDiesel 33DT	SisuDiesel 33DTA
Aspiration		Turbo	Turbo	Turbo	Turbo/Intercooled
Capacity	litre	3.3	3.3	3.3	3.3
Exhaust,					
- Side-mounted, vertical		●	●	●	●
- Horizontal		○	○	○	○
Dual, dry element air cleaner		●	●	●	●
Transmission					
12F/12R mechanical shuttle (30 km/h)		● (2WD)	● (2WD)	● (2WD)	● (2WD)
12F/12R mechanical shuttle (30 km/h)		○ (4WD)	○ (4WD)	○ (4WD)	○ (4WD)
24F/24R mechanical shuttle (40 km/h)		● (4WD)	● (4WD)	● (4WD)	● (4WD)
24F/24R PowerShuttle (40 km/h)		○ (4WD)	○ (4WD)	○ (4WD)	○ (4WD)
24F/24R mechanical shuttle and Speedshift (40 km/h)		○ (4WD)	○ (4WD)	○ (4WD)	○ (4WD)
Power take-off					
Operation and control		Cab	Semi-platform	Cab	Semi-platform
540 rpm @ 1938 engine rpm		○	●	○	●
540/540E @ 1938/1648 engine rpm		●	○	●	○
540/1000 @ 1938/1962 engine rpm		○	○	○	○
Ground speed PTO		○	○	○	○
Linkage and hydraulics					
3-point linkage		————— Top link sensing. Cat. 1/2 linkage with fixed ball ends (hook ends optional) —————			
Linkage control		————— Mechanical (Electronic, optional), with draft, position and rate-of-drop control —————			
Max. oil flow	litre/min ●	43.5	43.5	54.2	54.2
	litre/min ○	54.2	54.2	—	—
Max. pressure	bar	190	190	190	190
Levelling control, mechanical/hydraulic		●/○	●/○	●/○	●/○
Maximum lift capacity @ link ends, links horizontal	kg	2500	2500	2500	2500
Auxiliary hydraulics					
Spool valves (rear), cab/semi-platform		● 2/1	2/1	2/1	2/1
		○ Up to 3	Up to 3	Up to 3	Up to 3
Spool valves (mid-mounted)		○ 2	2	2	2
Steering					
Hydrostatic		●	●	●	●
Adjustable steering column					
- cab/semi-platform		●/○	●/○	●/○	●/○





		MF 3615	MF 3625	MF 3635	MF 3645
Brakes					
Type/actuation		Oil-cooled disc brakes, hydraulic actuation			
Parking brake		Mechanical, independent of main brakes. Hand lever operated			
Hydraulic trailer brakes		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
'Standard' wheels and tyres (A wide range of wheels and tyres is available. please consult your Dealer)					
Front - 2WD		7.50-16	7.50-16	7.50-16	7.50-16
- 4WD		11.2R24	11.2R24	11.2R24	11.2R24
Rear		16.9R30	16.9R30	16.9R30	16.9R30
Track adjustments (with 'Standard' wheels and tyres)					
Front - 2WD	mm	1435-2068	1435-2068	1435-2068	1435-2068
- 4WD	mm	1310-1938	1310-1938	1310-1938	1310-1938
Rear	mm	1198-1904	1198-1904	1198-1904	1198-1904
Standard equipment includes:					
Cab models		Rubber-mounted flat floor cab, vertical side exhaust, analogue/digital instrument panel, tinted glass, opening rear 3/4 and rear windows, cab heater, adjustable cloth-covered spring suspension seat with armrests, front and rear screen wash/wipe, 2 spool valves, 2 front and 2 rear work lights, aerial and speakers.			
Semi-platform models		Vertical side exhaust, adjustable vinyl-covered spring suspension seat with seat belt, 1 spool valve, 1 rear work light, 2-post folding safety frame.			
Variable equipment includes:					
Cab models		Horizontal exhaust*, passenger seat, air conditioning, opening front windscreen, pneumatic seat with armrests, 2 mid-mounted front work lights*, flashing beacon*, front weights*, wheel weights*, front fenders (or pivoting on 4WD models)*, rear fender extensions*, choice of drawbars/hitches*.			
Semi-platform models (plus * above)		Vinyl seat with armrests			
Weights and dimensions (approximate, 'standard' wheels and tyres, with fuel)					
Weight					
- 2WD cab	kg	2800	2800	2800	2800
- 2WD semi-platform	kg	2300	2300	2300	2300
- 4WD cab	kg	3200	3200	3200	3200
- 4WD semi-platform	kg	2500	2500	2500	2500
Length, links horizontal	m	3.74	3.74	3.74	3.74
Width, maximum	m	2.00	2.00	2.00	2.00
Height					
- over cab	m	2.51	2.51	2.51	2.51
- over exhaust	m	2.28	2.28	2.28	2.28
Ground clearance					
- under 4WD front axle	mm	390	390	390	390
Wheelbase	m	2.08	2.08	2.08	2.08
Turning circle (Inner radius, less brakes)					
- 2WD	m	3.73	3.73	3.73	3.73
- 4WD	m	4.35	4.35	4.35	4.35
Capacities					
Fuel tank capacity, cab/semi-platform	litre	110/83	110/83	110/83	110/83